

(۸
_	
(C

POST PILE FOUNDATION				SPREAD FOOTING						
NPS	"+"	Pedestal	Pile Dia	Pile Depth	Vertical Reinf	Pedestal	Footing Width x Length	Top	einforce Bottom	_
										L Bar
6	%2"	2'-10" x 2'-10"	30"	10'-0"	#6	2'-6" × 2'-6"	4'-0" × 6'-0"	#5	#5	#5
6	7/16"			10'-0"	#6		4'-0" x 7'-0"			
8	5/16"			10'-0"	#6		5'-0" x 8'-0"			
8	1/2"	+	+	11'-0"	#7	+	6'-0" × 9'-0"			+
10		3'-4" × 3'-4"	36"	13'-0"	#8	3'-0" x 3'-0"	7'-0" x 10'-0"	+	#8	#8
12				15'-0"	#10		7'-0" x 12'-0"	#6	#8	
14	+			15'-0"	#10		7'-0" x 13'-0"	#8	#9	
14	3/4"	· •	+	16'-0"	#10	į į	8'-0" x 14'-0"	#8	#9	,


"+" = Wall Thickness



ELEVATION



SECTION H-H




SECTION J-J
6 NPS THRU 14 NPS POSTS


PILE FOUNDATION

NOTES:

- 1. Backfill shall be in place prior to erection of post.
- 2. Slope protection required when indicated on the plans.
- Pile pedestal shall be formed 6" minimum below ground surface. Remainder to be placed against undisturbed material.







SPREAD FOOTING

STATE OF CALIFORNIA
DEPARTMENT OF TRANSPORTATION

OVERHEAD SIGNS-LIGHTWEIGHT FOUNDATION DETAILS

NO SCALE

S49

1-4-0